



### Application Adhesives

Typ	Appearance	Color Gardner	Bromine No.	Softening point	Acid value (mgKOH/g)
<u>Suntack UM-120</u>	light yellow	max.7	< 25	120 +/- 5 °C	< 0,03
<u>Suntack U90</u>	light yellow	max.7	< 25	100 +/- 5 °C	< 0,03
<u>Suntack U101</u>	light yellow	max.8	< 25	110 +/- 5 °C	< 0,03
<u>Suntack U 120</u>	light yellow	max.7	< 25	120 +/- 5 °C	< 0,03
<u>Suntack - U 140</u>	light yellow	max.8	< 25	140 +/- 5 °C	< 0,03

### Anwendung Gummi

Typ	Appearance	Color Gardner	Bromine No.	Softening point	Acid value (mgKOH/g)
<u>Suntack GS-90</u>	Amber	max.9	< 30	100 +/- 5 °C	< 0,03
<u>Suntack GA-100R</u>	Amber	max.12	< 30	100 +/- 5 °C	< 0,03
<u>Suntack GA 100</u>	Amber	max.12	< 30	105 +/- 5 °C	< 0,03

### Anwendung Farben und Lacke

Typ	Appearance	Color Gardner	Bromine No.	Softening point	Acid value (mgKOH/g)
<u>Suntack SK-120</u>	Amber	max.9	< 30	120 +/- 5 °C	< 0,03
<u>Suntack SK - 120W</u>	Amber	max.8	< 30	120 +/- 5 °C	< 0,03
<u>Suntack SK-120B</u>	Amber	max.12	< 30	120 +/- 5 °C	< 0,03

### Druckfarben

Typ	Appearance	Color Gardner	Bromine No.	Softening point	Acid value (mgKOH/g)
<u>Suntack YT-130</u>	Amber	max.9	< 30	130 +/- 5 °C	< 0,03
<u>Suntack YT-140</u>	Amber	max.9	< 30	140 +/- 5 °C	< 0,03